



Quality of life since 1825



Tub faucet Nautic – thermostat

150 c-c

Product features

- Safe Touch reduces the heat on the front of the faucet
- Maintains even water temperature
- Pull diverter changes flow path from bath to shower

Article numbers

Art-no.
GB41215333

EAN
7393792225663

Packaging information


Length: 395 mm | Width: 165 mm | Height: 90 mm
Weight: 2.66 kg
Weight: 1 pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.


Energy labeling and certifications

- Complies with Safe Water installation requirements.



Technical information

- Standard connection dimension: 150 c-c



- 1** Max flow (bath- and shower outlet)
- 2** Comfort flow
- 3** Bathtub outlet GB41636820, GB41638760
- 4** Bathtub outlet GB41636819, GB41638759
- 5** Shower set GB41103250

Valid for curve **1**

- Flowrate at 300 kPa:	0,46 l/s
- Pressure at flow 0,1 l/s:	14 kPa
- Pressure at flow 0,2 l/s:	57 kPa
- Pressure at flow 0,33 l/s:	154 kPa



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com