



Quality of life since 1825

Shower column Skandic Round

160 c-c

Product features

SAFE TOUCH



- Super slim head shower with generous water flow
- 3-functional hand shower with a pushbutton
- Mixer with smart features in a timeless design

Article numbers

Art-no.
GB41203230

EAN
7393792231299

Packaging information

Length: 714 mm | Width: 368 mm | Height: 94 mm

Weight: 5.4 kg

Weight: 1 pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Energy labeling and certifications



Technical information

- Standard connection dimension: 160 c-c




GUSTAVSBERG/

FLOW CHART/

SKANDIC SHOWER COLUMN ROUND

GUSTAVSBERG /
SMARTER BATHROOMS



- 1** Head shower
- 2** Hand shower
- 3** Bathtub outlet, spout GB41638759
- 4** Bathtub outlet, spout GB41638760
- 5** Hand shower outlet, spouts GB41638759, GB41638760

Valid for curve **1**

- Flowrate at 300 kPa:	0,375 l/s
- Pressure at flow 0,1 l/s:	21 kPa
- Pressure at flow 0,2 l/s:	85 kPa
- Pressure at flow 0,33 l/s:	231 kPa



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com