



Kitchen mixer New Nautic high Spout

Energy class B, G3/8 connection

Product features

ECO-FLOW

COLD-START









- Energy Class B
- · Cold-start, only cold water when the lever is in straight forward position
- Soft move, technology for smooth and precise handling

Article numbers

Art-no. GB41206056R EAN 7393792235471

Packaging information

Length: 440 mm | Width: 275 mm | Height: 75 mm

Weight: 1.7 kg Weight: 1 pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 70°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Energy labeling and certifications

















Technical information


- Max. tap capacity (at 300 kPa): 0,113 l/s
- CO2 Footprint: 7.37 kg
- Standard connection dimension: G10

GUSTAVSBERG/

FLOW CHART/

Kitchen mixer, energy class B New Nautic





1. Max flow

2. Dishwasher shut off valve

3. Optional aerator GB41638662 10

4. Optional aerator GB41638663 10

1. Max flow

- Flowrate at 300 kPa: 0,113 l/s
- Pressure at flow 0,1 l/s: 234 kPa
- Pressure at flow 0,2 l/s: N/A
- Pressure at flow 0,33 l/s: N/A

Rev, 2, 2020-12-21 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com