



Tub faucet Estetic - termostat

M. Black, fixed spout, downward connection, 160 c-c

Product features

SMART INSIDE

SAFE TOUCH







- · Safe Touch, minimizes the heat on the front of the mixer
- · Maintains even water temperature during temperature changes
- · Combines nicely with our various shower sets

Article numbers

Art-no. GB4120843353 EAN 7391530076232

Packaging information

Length: 292 mm | Width: 160 mm | Height: 74 mm

Weight: 2.35 kg Weight: 1 pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Energy labeling and certifications



Technical information


- Max. tap capacity (at 300 kPa): 0,4 l/s
- Pressure loss with flow (0,33 l/s) 204 kPa
- CO2 Footprint: 8.78 kg
- Standard connection dimension: 160 c-c

GUSTAVSBERG/

FLOW CHART/

Thermostatic Bathtub Mixers





- 1. Max flow bathtub outlet
- 2. Bathtub outlet
- 3. Shower set GB41106250

1. Max flow bathtub outlet

1. Max flow bathtub outlet			2. Bathtub outlet		
- Flow rate at 300 kPa:	0,4 l/s		- Flow rate at 300 kPa:	0,308 l/s	
- Pressure at flow 0,1 l/s:	19 kPa		- Pressure at flow 0,1 l/s:	32 kPa	
- Pressure at flow 0,2 l/s:	75 kPa		- Pressure at flow 0,2 l/s:	126 kPa	
- Pressure at flow 0,33 l/s:	204 kPa		- Pressure at flow 0,33 l/s:	344 kPa	

3. Shower set GB41106250

Γ	- Flow rate at 300 kPa:	0,1 l/s		
	- Pressure at flow 0,1 l/s:	300 kPa		
	- Pressure at flow 0,2 l/s:	N/A		
	- Pressure at flow 0,33 l/s:	N/A		

Rev, 1, 2022-12-22 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com