



Quality of life since 1825

# Dušisegisti New Nautic – termostaat, 40 c-c

Dušiühendus alla, veeühendus alla

## Toote Omadused

SMART INSIDE

SAFE TOUCH



- Safe Touch reduces the heat on the front of the mixer
- Maintains even water temperature during pressure and temperature changes
- Can be combined with bathtub spout

## Article number

Art.nr.  
GB41202404

EAN  
7391530075815

## Pakendiinfo

Pikkus: 292 mm | Laius: 95 mm | Kõrgus: 74 mm

Kaal: 1.9 kg

Number pakendis: 1 pc

## Paigaldus ja hooldus

Enne paigaldamist tuleb torude loputamiseks lasta veel joosta. Segisti on ühendatud paremalt külma veetoriga ja vasakult kuumaveetoriga. Veasure: max 1000 kPa, min 50 kPa. Kuuma vee temperatuur: max 80 °C, min 45 °C. Me ei vastuta valest paigaldusest tuleneva kahju eest.

## Energiamärgistus ja vastavustunnistused



## Tehniline info

- Max. tap capacity (at 300 kPa): 0,425 l/s
- Pressure loss with flow (0,33 l/s) 181 kPa
- CO<sub>2</sub>e jalajälg: 4,82 kg
- Ühenduse mõõdud: 40 c-c

# GUSTAVSBERG/

## FLOW CHART/ Thermostatic Mixers



- 1. Max flow (bath- and shower outlet)
- 2. Bathtub outlet: Spouts GB41650247, GB41650320
- 3. Shower set GB41106250
- 4. Spout GB41650279 (85 mm)

| 1. Max flow (bath- and shower outlet) |                              | 2. Bathtub outlet: Spouts GB41650247, GB41650320 |                              |
|---------------------------------------|------------------------------|--|------------------------------|
|                                       | - Flow rate at 300 kPa:      |  | - Flow rate at 300 kPa:      |
|                                       | 0,425 l/s                    |  | 0,322 l/s                    |
|                                       | - Pressure at flow 0,1 l/s:  |  | - Pressure at flow 0,1 l/s:  |
|                                       | 17 kPa                       |  | 29 kPa                       |
|                                       | - Pressure at flow 0,2 l/s:  |  | - Pressure at flow 0,2 l/s:  |
|                                       | 66 kPa                       |  | 116 kPa                      |
|                                       | - Pressure at flow 0,33 l/s: |  | - Pressure at flow 0,33 l/s: |
|                                       | 181 kPa                      |  | 316 kPa                      |

  

| 3. Shower set GB41106250 |                              | 4. Spout GB41650279 (85 mm) |                              |
|--------------------------|------------------------------|-----------------------------|------------------------------|
|                          | - Flow rate at 300 kPa:      |                             | - Flow rate at 300 kPa:      |
|                          | 0,1 l/s                      |                             | 0,265 l/s                    |
|                          | - Pressure at flow 0,1 l/s:  |                             | - Pressure at flow 0,1 l/s:  |
|                          | 300 kPa                      |                             | 43 kPa                       |
|                          | - Pressure at flow 0,2 l/s:  |                             | - Pressure at flow 0,2 l/s:  |
|                          | N/A                          |                             | 171 kPa                      |
|                          | - Pressure at flow 0,33 l/s: |                             | - Pressure at flow 0,33 l/s: |
|                          | N/A                          |                             | 465 kPa                      |

Rev, 1, 2022-12-28 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / [www.gustavsberg.com](http://www.gustavsberg.com) / [info@gustavsberg.com](mailto:info@gustavsberg.com)