



Quality of life since 1825

Dušas maisītājs New Nautic – ar termostatu, 40 c-c

Izvide lejpvērsta, savienojums lejpvērsts

Produkta īpašības

SMART INSIDE

SAFE TOUCH



- Safe Touch reduces the heat on the front of the mixer
- Maintains even water temperature during pressure and temperature changes
- Can be combined with bathtub spout

Article number

Art.nr.
GB41202404

EAN
7391530075815

Pakuotēs informācija

Garums: 292 mm | Platums: 95 mm | Augstums: 74 mm

Svoris: 1.9 kg

Pakuotēs numeris: 1 pc

Montāža un kopšana

Pirms uzstādīšanas caurules ir jāpievada līdz ūdens jaucējkrānam. Ūdens jaucējkrāns tiek pievienots aukstā ūdens padeves caurulei labajā pusē un karstā ūdens padeves caurulei kreisajā pusē. Ūdens spiediens: maks. 1000 kPa, min. 50 kPa. Karstā ūdens temperatūra: maks. 80 °C, min. 45 °C. Ņemiet vērā, ka mēs neuzņemamies atbildību par bojājumiem, kas radušies nepareizas uzstādīšanas rezultātā.

Enerģijas marķējums un sertifikāti



Techninē informācija

- Max. tap capacity (at 300 kPa): 0,425 l/s
- Pressure loss with flow (0,33 l/s) 181 kPa
- CO2e pēdas nospiedums: 4.82
- Standarta savienojuma dimensija: 40 c-c

GUSTAVSBERG/

FLOW CHART/ Thermostatic Mixers



- 1. Max flow (bath- and shower outlet)
- 2. Bathtub outlet: Spouts GB41650247, GB41650320
- 3. Shower set GB41106250
- 4. Spout GB41650279 (85 mm)

| 1. Max flow (bath- and shower outlet) | | 2. Bathtub outlet: Spouts GB41650247, GB41650320 | |
|---------------------------------------|-----------|--|-----------|
| - Flow rate at 300 kPa: | 0,425 l/s | - Flow rate at 300 kPa: | 0,322 l/s |
| - Pressure at flow 0,1 l/s: | 17 kPa | - Pressure at flow 0,1 l/s: | 29 kPa |
| - Pressure at flow 0,2 l/s: | 66 kPa | - Pressure at flow 0,2 l/s: | 116 kPa |
| - Pressure at flow 0,33 l/s: | 181 kPa | - Pressure at flow 0,33 l/s: | 316 kPa |

| 3. Shower set GB41106250 | | 4. Spout GB41650279 (85 mm) | |
|------------------------------|---------|------------------------------|-----------|
| - Flow rate at 300 kPa: | 0,1 l/s | - Flow rate at 300 kPa: | 0,265 l/s |
| - Pressure at flow 0,1 l/s: | 300 kPa | - Pressure at flow 0,1 l/s: | 43 kPa |
| - Pressure at flow 0,2 l/s: | N/A | - Pressure at flow 0,2 l/s: | 171 kPa |
| - Pressure at flow 0,33 l/s: | N/A | - Pressure at flow 0,33 l/s: | 465 kPa |

Rev, 1, 2022-12-28 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com