



Quality of life since 1825

Suihkusekoitin Nordic – termostaatti

Ulostulo alaspäin, 160 c-c

Tuotteen ominaisuudet

SMART INSIDE

SAFE TOUCH



- Safe Touch reduces the heat on the front of the mixer
- Maintains even water temperature during pressure and temperature changes
- Can be completed with bathtub spout

Artikkelien numero

Art.nr.
GB41201704

EAN
7391530076997

Pakkaustiedot

Pituus: 292 mm | Leveys: 95 mm | Korkeus: 74 mm


Paino: 1.63 kg

Pakkauksen numero: 1 pc

Kokoaminen & hoito

Putket on huuhdottava ennen asennusta. Hana kytketään oikealta kylmävesijohtoon ja vasemmalta kuumavesijohtoon. Vedenpaine: enintään 1000 kPa, vähintään 50 kPa. Kuuman veden lämpötila: enintään 80 °C, vähintään 45 °C. Huomaathan, että emme vastaa vahingoista, jotka johtuvat virheellisestä asennuksesta.


Energiamerkintä ja -sertifiointi



Tekniset tiedot

- Max. tap capacity (at 300 kPa): 0,425 l/s
- Pressure loss with flow (0,33 l/s) 181 kPa
- Tuotteen CO2e jalanjälki: 4,77 kg
- Liitäntäkoko: 160 c-c

Varaosat



ExplodedView Nordic_thermomixer_mixers (Rev 1. 2023-02-07)

Nr.	Tuote	Art.nr.
1	Kahva Nordic – määrä	GB4165022901
3	Ohjain Nautic	GB41650292001
4		GB41638334 01
5	Kahva Nordic – lämpötila	GB4165023101
7	Nippa Nautic	GB4165020401
8		GB41634719 01
9	Nippa Nautic	GB4165020601
10		GB41632698 02
11	Tiiviste Nautic	GB41650355
12		GB41635633 02
13		GB41635633 10
14		GB41638542 01
15		GB41636822 01
16		GB41634555 01
17	Vaihdin	GB41636577 01
18		GB41630131 01
19	Kääntyvä juoksuputki 85 mm	GB41650279
20	Kääntyvä juoksuputki 150 mm	GB41650282
21	Kääntyvä juoksuputki 250 mm	GB41650285
22	Kääntyvä juoksuputki 350 mm	GB41650288
23		GB41633972
26	Ajastettu painoventtiili	GB41639716
27	Hylly	GB41650052
28	Hylly	GB4165005253
31	Vaihdin N Nautic	GB4165021301

GUSTAVSBERG/

FLOW CHART/ Thermostatic Mixers



- 1. Max flow (bath- and shower outlet)
- 2. Bathtub outlet: Spouts GB41650247, GB41650320
- 3. Shower set GB41106250
- 4. Spout GB41650279 (85 mm)

1. Max flow (bath- and shower outlet)	2. Bathtub outlet: Spouts GB41650247, GB41650320
- Flow rate at 300 kPa:	- Flow rate at 300 kPa:
0,425 l/s	0,322 l/s
- Pressure at flow 0,1 l/s:	- Pressure at flow 0,1 l/s:
17 kPa	29 kPa
- Pressure at flow 0,2 l/s:	- Pressure at flow 0,2 l/s:
66 kPa	116 kPa
- Pressure at flow 0,33 l/s:	- Pressure at flow 0,33 l/s:
181 kPa	316 kPa

3. Shower set GB41106250	4. Spout GB41650279 (85 mm)
- Flow rate at 300 kPa:	- Flow rate at 300 kPa:
0,1 l/s	0,265 l/s
- Pressure at flow 0,1 l/s:	- Pressure at flow 0,1 l/s:
300 kPa	43 kPa
- Pressure at flow 0,2 l/s:	- Pressure at flow 0,2 l/s:
N/A	171 kPa
- Pressure at flow 0,33 l/s:	- Pressure at flow 0,33 l/s:
N/A	465 kPa

Rev, 1, 2022-12-28 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com