



Quality of life since 1825

# Dušas maisītājs Atlantic – ar termostatu

Izvide lejpurvērsta, 160 c-c

## Produkta īpašības

SMART INSIDE

SAFE TOUCH



- Safe Touch reduces the heat on the front of the mixer
- Maintains even water temperature during pressure and temperature changes
- Can be completed with Gustavsberg bathtub spout

## Article number

Art.nr.  
GB41201304

EAN  
7391530075785

## Pakuotēs informācija

Garums: 292 mm | Platums: 95 mm | Augstums: 74 mm

Svoris: 1.66 kg

Pakuotēs numeris: 1 pc

## Montāža un kopšana

Pirms uzstādīšanas caurules ir jāpievada līdz ūdens jaucējkrānam. Ūdens jaucējkrāns tiek pievienots aukstā ūdens padeves caurulei labajā pusē un karstā ūdens padeves caurulei kreisajā pusē. Ūdens spiediens: maks. 1000 kPa, min. 50 kPa. Karstā ūdens temperatūra: maks. 80 °C, min. 45 °C. Ņemiet vērā, ka mēs neuzņemamies atbildību par bojājumiem, kas radušies nepareizas uzstādīšanas rezultātā.

## Enerģijas marķējums un sertifikāti



## Techninē informācija

- Max. tap capacity (at 300 kPa): 0,425 l/s
- Pressure loss with flow (0,33 l/s) 181 kPa
- CO2e pēdas nospiedums: 4.97
- Standarta savienojuma dimensija: 160 c-c

# GUSTAVSBERG/

## FLOW CHART/ Thermostatic Mixers



- 1. Max flow (bath- and shower outlet)
- 2. Bathtub outlet: Spouts GB41650247, GB41650320
- 3. Shower set GB41106250
- 4. Spout GB41650279 (85 mm)

1. Max flow (bath- and shower outlet)	2. Bathtub outlet: Spouts GB41650247, GB41650320
- Flow rate at 300 kPa:	- Flow rate at 300 kPa:
0,425 l/s	0,322 l/s
- Pressure at flow 0,1 l/s:	- Pressure at flow 0,1 l/s:
17 kPa	29 kPa
- Pressure at flow 0,2 l/s:	- Pressure at flow 0,2 l/s:
66 kPa	116 kPa
- Pressure at flow 0,33 l/s:	- Pressure at flow 0,33 l/s:
181 kPa	316 kPa

3. Shower set GB41106250	4. Spout GB41650279 (85 mm)
- Flow rate at 300 kPa:	- Flow rate at 300 kPa:
0,1 l/s	0,265 l/s
- Pressure at flow 0,1 l/s:	- Pressure at flow 0,1 l/s:
300 kPa	43 kPa
- Pressure at flow 0,2 l/s:	- Pressure at flow 0,2 l/s:
N/A	171 kPa
- Pressure at flow 0,33 l/s:	- Pressure at flow 0,33 l/s:
N/A	465 kPa

Rev, 1, 2022-12-28 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / [www.gustavsberg.com](http://www.gustavsberg.com) / [info@gustavsberg.com](mailto:info@gustavsberg.com)