



Quality of life since 1825

Shower package Atlantic 2.1 – Thermostat

Incl. Shower set, lead-free, energy class A, 150 c-c

Product features

SMART INSIDE



SAFE TOUCH



LEAD-FREE



- Safe Touch, minimizes the heat on the front of the mixer
- Even water temperature during pressure and temperature changes
- Contains less than 0.1% lead

Article numbers

Art-no.
GB412113870

EAN
7391530076461

Packaging information

Length: 775 mm | Width: 145 mm | Height: 80 mm

Weight: 3 kg

Weight: 1 pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.


Energy labeling and certifications



Technical information

- Max. tap capacity (at 300 kPa): 0,1l/s
- Pressure loss with flow (0,1l/s) 300 kPa
- CO2 Footprint: 15.7 kg
- Standard connection dimension: 150 c-c

Spare parts



ExplodedView GB41106250_Shower_set_2.1 (Rev 1. 2023-04-05)

No.	Product	Art-no.
1	Shower handle 2.1/2.2	GB4165036401
2	Flow regulator	GB4165036501
3	Shower hose Original	GB41636266 00
4	Slider 25 mm	GB41638726 01
5	Wall bracket / mounting details	GB41638727 02
6	Soap cup 25 mm	GB41638728 01
7	Drain valve Care	GB41638960 01
8	Bracket for shower set	GB41637850 02
9	Wall Distance Shower set	GB4165037201
10	Check valve dw 14	GB41634719 01

GUSTAVSBERG/

FLOW CHART/ Thermostatic Mixers



- 1. Max flow (bath- and shower outlet)
- 2. Bathtub outlet: Spouts GB41650247, GB41650320
- 3. Shower set GB41106250
- 4. Spout GB41650279 (85 mm)

1. Max flow (bath- and shower outlet)		2. Bathtub outlet: Spouts GB41650247, GB41650320	
- Flow rate at 300 kPa:	0,425 l/s	- Flow rate at 300 kPa:	0,322 l/s
- Pressure at flow 0,1 l/s:	17 kPa	- Pressure at flow 0,1 l/s:	29 kPa
- Pressure at flow 0,2 l/s:	66 kPa	- Pressure at flow 0,2 l/s:	116 kPa
- Pressure at flow 0,33 l/s:	181 kPa	- Pressure at flow 0,33 l/s:	316 kPa

3. Shower set GB41106250		4. Spout GB41650279 (85 mm)	
- Flow rate at 300 kPa:	0,1 l/s	- Flow rate at 300 kPa:	0,265 l/s
- Pressure at flow 0,1 l/s:	300 kPa	- Pressure at flow 0,1 l/s:	43 kPa
- Pressure at flow 0,2 l/s:	N/A	- Pressure at flow 0,2 l/s:	171 kPa
- Pressure at flow 0,33 l/s:	N/A	- Pressure at flow 0,33 l/s:	465 kPa

Rev, 1, 2022-12-28 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com