



Quality of life since 1825



Shower column Nordic Square

Connection up and down, 160 c-c with shower column Square

Product features

SMART INSIDE SAFE TOUCH



- Safe Touch, minimizes the heat on the front of the mixer
- Maintains even water temperature during pressure and temperature changes
- Can be supplemented with reverse pipe

Article numbers

Art-no.
GB41201735

EAN
7391530077017

Packaging information

Length: 745 mm | Width: 368 mm | Height: 94 mm

Weight: 4.9 kg

Weight: 1pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Energy labeling and certifications



CERTIFYING
KONTROLL
RISE



Denna produkt är uppmärksammad till
Branschregler Säker Vatteninstallations
2021:1. Leverantören garanterar
produkten funktion om branschreglerna
och monteringsanvisningarna följs.




Technical information

- Max. tap capacity (at 300 kPa): 0,425 l/s
- Pressure loss with flow (0,33 l/s) 181 kPa
- Standard connection dimension: 160 c-c

GUSTAVSBERG/

FLOW CHART/

Thermostatic Mixers, Shower Columns, Spout 350 mm



█ 1. Max flow (bath- and shower outlet) █ 2. Head shower GB41103230, GB41103235 █ 3. Hand shower GB41103230, GB41103235	█ 4. Spout GB41650288 (350 mm)
---	---

1. Max flow (bath- and shower outlet)	2. Head shower GB41103230, GB41103235
- Flow rate at 300 kPa: 0,465 l/s	- Flow rate at 300 kPa: 0,425 l/s
- Pressure at flow 0,1 l/s: 14 kPa	- Pressure at flow 0,1 l/s: 17 kPa
- Pressure at flow 0,2 l/s: 56 kPa	- Pressure at flow 0,2 l/s: 66 kPa
- Pressure at flow 0,33 l/s: 151 kPa	- Pressure at flow 0,33 l/s: 181 kPa

3. Hand shower GB41103230, GB41103235	4. Spout GB41650288 (350 mm)
- Flow rate at 300 kPa: 0,175 l/s	- Flow rate at 300 kPa: 0,273 l/s
- Pressure at flow 0,1 l/s: 98 kPa	- Pressure at flow 0,1 l/s: 40 kPa
- Pressure at flow 0,2 l/s: 392 kPa	- Pressure at flow 0,2 l/s: 161 kPa
- Pressure at flow 0,33 l/s: N/A	- Pressure at flow 0,33 l/s: 437 kPa

Rev, 1, 2022-12-28 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com