Quality of life since 1825

Shower column Nordic Square

150 c-c

Product features

SMART INSIDE SAFE TOUCH

- Safe Touch, minimizes the heat on the front of the mixer
- Maintains even water temperature during pressure and temperature changes
- Can be supplemented with reverse pipe

Article numbers

Art-no.	EAN
GB41211735	7391530077055

Packaging information

Length: 745 mm | Width: 368 mm | Height: 94 mm
Weight: 4.94 kg
Weight: 1 pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Energy labeling and certifications

1002 CERTIFIERING KONTROLL RI. SE

STF

Denna produkt är anpassad till Branschregler Säker Vatteninstallation 2021:1. Leverantören garanterar produktens funktion om branschreglerna och monteringsanvisningarna följs.

EB

PRODUKTSERTIFIKAT SINTEF Certification

Technical information

- Max. tap capacity (at 300 kPa): 0,425 l/s
- Pressure loss with flow (0,33 l/s) 181 kPa
- Standard connection dimension: 150 c-c

Spare parts



No.	Product	Art-no.
2	Hand shower, Square	GB41639441
3	Head shower Square, matte black	GB41639443 53
4	Wall bracket Round/Square, matte black	GB41639444 53
5	Slider 22 mm	GB41639445
6	Gasket set	GB41639446
7	Elevation of head shower rod	GB41639512
8	Soap shelf	GB41639513
9	Shower hose matt black	GB41637572 53
10	Slides ø22 matt black	GB41639445 53

GUSTAVSBERG/

FLOW CHART/

Thermostatic Mixers, Shower Columns, Spout 350 mm



1. Max flow (bath- and shower outlet)
2. Head shower GB41103230, GB41103235
3. Hand shower GB41103230, GB41103235
4. Spout GB41650288 (350 mm)

1. Max flow (bath- and shower outlet)	
- Flow rate at 300 kPa:	0,465 l/s
- Pressure at flow 0,1 l/s:	14 kPa
- Pressure at flow 0,2 l/s:	56 kPa
- Pressure at flow 0,33 l/s:	151 kPa

2. Head shower GB41103230, GB41103235	
- Flow rate at 300 kPa:	0,425 l/s
- Pressure at flow 0,1 l/s:	17 kPa
- Pressure at flow 0,2 l/s:	66 kPa
- Pressure at flow 0,33 l/s:	181 kPa

3. Hand shower GB41103230, GB41103235	
- Flow rate at 300 kPa:	0,175 l/s
- Pressure at flow 0,1 l/s:	98 kPa
- Pressure at flow 0,2 l/s:	392 kPa
- Pressure at flow 0,33 l/s:	N/A

4. Spout GB41650288 (350 mm)	
- Flow rate at 300 kPa:	0,273 l/s
- Pressure at flow 0,1 l/s:	40 kPa
- Pressure at flow 0,2 l/s:	161 kPa
- Pressure at flow 0,33 l/s:	437 kPa

Rev, 1, 2022-12-28 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com