



Quality of life since 1825

# Shower package New Nautic 2.1 - Termostat

Inkl. shower set, energy class A, 150 c-c

## Product features

SMART INSIDE

SAFE TOUCH



- Safe Touch reduces the heat on the front of the faucet
- Maintains even water temperature
- Complete with shower set energy class A

## Article numbers

Art-no.  
GB41212387

EAN  
7391530075891

## Packaging information

Length: 775 mm | Width: 145 mm | Height: 80 mm

Weight: 2.94 kg


Weight: 1 pc

## Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

## Energy labeling and certifications

- Complies with Safe Water installation requirements.



## Technical information

- Max. tap capacity (at 300 kPa): 0,1l/s
- Pressure loss with flow (0,1l/s) 300 kPa
- Standard connection dimension: 150 c-c

# Spare parts



ExplodedView New Nautic\_thermomixer\_mixers (Rev 1. 2023-02-07)



| No. | Product                             | Art-no.       |
|-----|-------------------------------------|---------------|
| 1   | Handle New Nautic - quantity        | GB4165021701  |
| 3   | Headwork New Nautic                 | GB41650292001 |
| 4   | Thermostat cartridge                | GB41638334 01 |
| 5   | Handle New Nautic - temperature     | GB4165021901  |
| 7   | Nipple New Nautic                   | GB4165020401  |
| 8   | Check valve dw 14                   | GB41634719 01 |
| 9   | Nipple New Nautic                   | GB4165020601  |
| 10  | Check valve with filter             | GB41632698 02 |
| 11  | Gasket New Nautic                   | GB41650355    |
| 12  | Filter for non-return valve         | GB41635633 02 |
| 13  | Filter for non-return valve         | GB41635633 10 |
| 14  | Aerator                             | GB41638542 01 |
| 15  | Pull switch                         | GB41636822 01 |
| 16  | Aerator                             | GB41634555 01 |
| 17  | Pull diverter                       | GB41636577 01 |
| 18  | Aerator 24x1                        | GB41630131 01 |
| 19  | Swivel spout 85 mm                  | GB41650279    |
| 20  | Swivel spout 150 mm                 | GB41650282    |
| 21  | Swivel spout 250 mm                 | GB41650285    |
| 22  | Swivel spout 350 mm                 | GB41650288    |
| 23  | Details for swivel limitation       | GB41633972    |
| 24  | Handle New Nautic Care - quantity   | GB4165022101  |
| 25  | Handle New Nautic Care - temprature | GB4165022301  |
| 26  | Time Valve                          | GB41639716    |
| 27  | Shelf                               | GB41650052    |
| 28  | Shelf, Matt black                   | GB4165005253  |
| 29  | Handle New Nautic - quantity        | GB4165036301  |
| 30  | Diverter New Nautic                 | GB4165035201  |
| 31  | Diverter New Nautic                 | GB4165021301  |
| 32  | Aerator                             | GB4165021001  |
| 33  | Connection nipple                   | GB41634756 01 |
| 35  | Details for 207420                  | GB41634577    |
| 36  | Plug                                | GB41638998 02 |
| 37  | Connection nipple complete          | GB41632815    |

# GUSTAVSBERG/

## FLOW CHART/ Thermostatic Mixers



- 1. Max flow (bath- and shower outlet)
- 2. Bathtub outlet: Spouts GB41650247, GB41650320
- 3. Shower set GB41106250
- 4. Spout GB41650279 (85 mm)

| 1. Max flow (bath- and shower outlet) | 2. Bathtub outlet: Spouts GB41650247, GB41650320 |
|---------------------------------------|--|
| - Flow rate at 300 kPa: 0,425 l/s     | - Flow rate at 300 kPa: 0,322 l/s                |
| - Pressure at flow 0,1 l/s: 17 kPa    | - Pressure at flow 0,1 l/s: 29 kPa               |
| - Pressure at flow 0,2 l/s: 66 kPa    | - Pressure at flow 0,2 l/s: 116 kPa              |
| - Pressure at flow 0,33 l/s: 181 kPa  | - Pressure at flow 0,33 l/s: 316 kPa             |

| 3. Shower set GB41106250            | 4. Spout GB41650279 (85 mm)          |
|-------------------------------------|--------------------------------------|
| - Flow rate at 300 kPa: 0,1 l/s     | - Flow rate at 300 kPa: 0,265 l/s    |
| - Pressure at flow 0,1 l/s: 300 kPa | - Pressure at flow 0,1 l/s: 43 kPa   |
| - Pressure at flow 0,2 l/s: N/A     | - Pressure at flow 0,2 l/s: 171 kPa  |
| - Pressure at flow 0,33 l/s: N/A    | - Pressure at flow 0,33 l/s: 465 kPa |

Rev, 1, 2022-12-28 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / [www.gustavsberg.com](http://www.gustavsberg.com) / [info@gustavsberg.com](mailto:info@gustavsberg.com)