



Quality of life since 1825

Shower mixer Atlantic - Single lever

Shower connection downwards, 150 c-c

Product features

- Grip-friendly lever with clear color marking for hot and cold water
- Soft move, ceramic package with smooth and precise operation
- Eco-stop, adjustable maximum flow limitation

Article numbers

Art-no.
GB41211314

EAN
7391530084817

Packaging information

Length: 210 mm | Width: 145 mm | Height: 92 mm
Weight: 1.96 kg
Weight: 1pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Energy labeling and certifications



Technical information


- Max. tap capacity (at 300 kPa): 0,37 l/s
- Pressure loss with flow (0,1l/s) 22 kPa
- Standard connection dimension: 150 c-c

GUSTAVSBERG/

FLOW CHART/

Ettgrepp väggblandare Nya Nautic

GUSTAVSBERG /
SMARTER BATHROOMS



	1. Max flow
	2. GB41212087, GB41202087, (with shower set GB41106250)
	3. A-restrictor

4. B-restrictor

1. Max flow		2. GB41212087, GB41202087, (with shower set GB41106250)	
- Flow rate at 300 kPa:	0,367 l/s	- Flow rate at 300 kPa:	0,1 l/s
- Pressure at flow 0,1 l/s:	22 kPa	- Pressure at flow 0,1 l/s:	300 kPa
- Pressure at flow 0,2 l/s:	89 kPa	- Pressure at flow 0,2 l/s:	N/A
- Pressure at flow 0,33 l/s:	243 kPa	- Pressure at flow 0,33 l/s:	N/A

Rev, 1, 2023-05-22 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com