

# Bidé mixer Atlantic

With waste valve and lift bar

#### **Product features**

ECO-STOP

QUICK FIT

SMART INSIDE







- · All components made in food approved materials
- · Ball-jointed aerator directs the water flow
- · Easy grip lever with clear colour marking for hot and cold

#### Article numbers

Art-no. GB41215072 EAN 7391530084862

## Packaging information

Length: 225 mm | Width: 205 mm | Height: 70 mm

Weight: 1.2 kg Weight: 1 pc

## Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 70°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

## Energy labeling and certifications








#### Technical information

- Max. tap capacity (at 300 kPa): 0,123 l/s
- Pressure loss with flow (0,11/s) 197 kPa
- Standard connection dimension: 10mm

# GUSTAVSBERG/

# FLOW CHART/ Bidet mixer New Nautic





1. Max flow

#### 1. Max flow

ı	- Flowrate at 300 kPa:	0,123 l/s
	- Pressure at flow 0,1 l/s:	197 kPa
	- Pressure at flow 0,2 l/s:	N/A
	- Pressure at flow 0,33 l/s:	N/A

Rev, 1, 2021-02-08 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com