



Livskvalitet siden 1825

Takdusj Ducentic

150 c-c

Produktets funksjoner

- Inspirert av tradisjonell og moderne design
- Flott dusjopplevelse
- Tilgjengelig i polert messing og krom

Artikkelnummer

Art.nr.
GB41217036


EAN
7391530088068

Informasjon om pakking

Lengde: 745 mm | Bredde: 368 mm | Høyde: 94 mm
Vekt: 5.6 kg
Antall i pakken: 1 st


Montering og vedlikehold

Energimerking og sertifiseringer



Teknisk informasjon


- Max. tap capacity (at 300 kPa): 0,402 l/s
- Pressure loss with flow (0,33 l/s) 203 kPa



GUSTAVSBERG/

FLOW CHART/

Ducentic shower column



- 1. Max flow (bath and shower outlet)
- 2. Ducentic hand shower
- 3. Ducentic head shower
- 4. Ducentic hand shower + diverter spout GB41650638
- 5. Diverter spout GB41650638, bath outlet

1. Max flow (bath and shower outlet)

- Flow rate at 300 kPa:	0,402 l/s
- Pressure at flow 0,1 l/s:	19 kPa
- Pressure at flow 0,2 l/s:	74 kPa
- Pressure at flow 0,33 l/s:	203 kPa

2. Ducentic hand shower

- Flow rate at 300 kPa:	0,122 l/s
- Pressure at flow 0,1 l/s:	203 kPa
- Pressure at flow 0,2 l/s:	811 kPa
- Pressure at flow 0,33 l/s:	N/A

3. Ducentic head shower

- Flow rate at 300 kPa:	0,18 l/s
- Pressure at flow 0,1 l/s:	93 kPa
- Pressure at flow 0,2 l/s:	370 kPa
- Pressure at flow 0,33 l/s:	N/A

4. Ducentic hand shower + diverter spout GB41650638

- Flow rate at 300 kPa:	0,117 l/s
- Pressure at flow 0,1 l/s:	220 kPa
- Pressure at flow 0,2 l/s:	882 kPa
- Pressure at flow 0,33 l/s:	N/A

5. Diverter spout GB41650638, bath outlet

- Flow rate at 300 kPa:	0,367 l/s
- Pressure at flow 0,1 l/s:	22 kPa
- Pressure at flow 0,2 l/s:	89 kPa
- Pressure at flow 0,33 l/s:	243 kPa

Rev, 1, 2025-12-16 Gustavsberg Lab

Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com