



Quality of life since 1825



Kitchen mixer Estetic

Lead-free, DW shut-off

Product features



- Maximum flexibility with a pivoting spout, makes cooking and washing up easier. Locks for 0°, 60° and 110° are included
- Cold start technology for energy efficiency and comfort – eliminates unnecessary heat consumption and provides a safe mixer even for children
- Made from high quality materials and equipped with water saving technology to reduce environmental impact without compromising on performance or style

Article numbers

Art-no.
GB41208096

EAN
7391530091600

Packaging information

Length: 545 mm | Width: 350 mm | Height: 70 mm

Weight: 2.75 kg

Weight: 1pc

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Energy labeling and certifications




Technical information

- Pressure, Flow & Temp: Maxflöde 300kPa: 0,1l/s
- Standard connection dimension: G3/8

GUSTAVSBERG/

FLOW CHART/

Estetic kitchen L-spout with dishwasher



- 1. Spout
- 2. Dishwasher valve

| 1. Spout | |
|----------|-------------------------------------|
| | - Flowrate at 300 kPa: 0,1 l/s |
| | - Pressure at flow 0,1 l/s: 300 kPa |
| | - Pressure at flow 0,2 l/s: N/A |
| | - Pressure at flow 0,33 l/s: N/A |

Rev, 1, 2025-11-06 Gustavsberg Labb

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg / Phone +46 (0)8-570 391 00 / www.gustavsberg.com / info@gustavsberg.com