



Quality of life since 1825

Wall-hung toilet Public 6622 – with cistern, HygienicFlush

4 Litre, no seat, C+

Product features

CERAMICPLUS

QUIET AND DRY
QUIET AND DRY



- Durable stainless steel push button suitable for public environments
- Open flush edge for simplified cleaning
- Ceramicplus for quick and easy cleaning

Article numbers

Art-no.
GB1166224R1505

EAN
7391530094984

Packaging information

Length: 900 mm | Width: 360 mm | Height: 900 mm


Weight: 32 kg

Weight: 1 pc

Assembling & Care


Mounted with bolts directly on the wall. Washers, bushings and nuts included (M12) but not bolts. Bolt projection from finished wall must be 60 ± 2mm. Rubber bellows for waste pipe connection included. See supplied installation instructions and mounting kit for each toilet. Triomont fixture for wall hung toilet and bidet RSK 382 57 56, is recommended for installation on weak walls. According to the AMA the seat height should be 450 mm which corresponds to 270 mm distance (centre-centre) between the existing floor and the centre of the drain.

Energy labeling and certifications



Technical information

- Flushing – water quantity: 4 Enkelspolning 4 (L) Dual flush 4/2 (L)
- Trap à Outlet: Wall connection
- Standard connection dimension: c/c 155mm sitsfäste






SMARTER
BATHROOMS

FLOW CHART

FILL VALVE - 9GN00100



A MEMBER OF THE
VILLEROY & BOCH GROUP

Villeroy & Boch Gustavsberg AB
Box 400, 134 29 Gustavsberg
Phone +46 (0)8-570 391 00
www.gustavsberg.com | info@gustavsberg.com